Construction: • Stainless Steel Frame

Hanna's Angled Side & Window Brush

is similar to the Horizontal Side & Window Brush, only angled toward the vehicle to follow the contour of its surface. It uses a combination of gravity and a special dampening shock to provide proper brush penetration and safely clean hard to reach areas like the top of the vehicle's side windows. The 70" brush height in combination with the angled brush assembly allows better cleaning of the top side window area of sport utility vehicles and mini vans.

- All stainless steel frame construction.
- ASWB has a 70" (1.78m) brush assembly
- One size fits all with 122" of physical clearance for all standard vehicles
- Hydraulic Drive
- Gravity operated with cushioning shock
- Includes spray manifold and jets
- Includes Water & Hydraulic Plumbing
- ASWB supplied with shock pivot system standard
- Pneumatic Retracts are not available
- Hydraulic flow controls and solenoid valves are included in proportionator pricing or purchased separately

- Operating Space Required 7' (213 cm)
- *Brush Height* 70" (177.80 cm)
- Overall Height 10'6" (3.21 m

Brush Dimensions:

Top Brush	24"/28" X 42"
Panel	(61 cm/71 cm x 107 cm)
Bottom Brush	22"/18.5" X 28"
Panel	(56 cm/47 cm x 71 cm)
Top Core	8" x 42" (20.32 cm x 107 cm)
Bottom Core	10" x 28" (25.40 cm x 71 cm)

Technical Data:

Hydraulic	3.0 GPM
Flow	(11.4 LPM)
Speed	40 – 50 RPM
Brush Material	Hanna Soft Cloth
	Foam
	Neoglide Brush